

# Manómetros



**PAG/PSQ** Sanitario

2.5" (63mm)  
4" (100mm)

316L SS

316 SS, Electropulido con Tri-Clamp® de 0.75", 1.5" or 2"

Vac-0-1,000 psi/bar



**PAM** Ammonia (Amoniaco)

2.5" (63mm), 3.5" (90mm),  
4" (100mm), 6" (150mm),  
8.5" (215mm), 10" (250mm)

316L SS

¼" NPT

Vac-0-300 psi/°F



**PBC** Caja de Latón Reforzado

2.5" (63mm)  
4" (100mm)

Latón

2.5" carátula: ¼" NPT  
4" carátula: ¼", ½" NPT

Vac-0-10,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PCC** Código de Colores

4" (100mm)

316 L SS/Bronce al Fósforo/Latón

¼" o ½" NPT

Vac-0-20,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PCT/PCT-LF** Contratista

4.5" (115mm)

Bronce al Fósforo/Latón o Latón al Fósforo sin Plomo/Latón

¼" NPT

Vac-0-5,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PFP** Premium LF

2.5" (63mm)  
4" (100mm), 4.5" (115mm)  
6" (150mm)  
Aro Bayoneta

316 SS

2.5" carátula: ¼" NPT  
4" carátula: ¼", ½" NPT, ½"  
BSP(G), 9/16" HP/HP autoclave  
6" carátula: ¼", ½" NPT

Vac-0-40,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PFP-ZR** Premium StabilizR™

2.5" (63mm)  
4" (100mm)  
6" (150mm)

316 SS

2.5" carátula: ¼" NPT  
4" carátula: ¼", ½" NPT  
6" carátula: ¼", ½" NPT

Vac-0-20,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PFQ/PFQ-LF** Lleno

1.5" (40mm), 2" (50mm)  
2.5" (63mm)  
4" (100mm)  
Cierre Repujado

316 SS/Bronce al Fósforo or  
AISI 316 SS/Latón al Fósforo  
sin Plomo

1.5" carátula: ⅙" NPT  
2" carátula: ⅛", ¼" NPT  
2.5" carátula: ¼" NPT, 7/16"-20 SAE  
4" carátula: ¼", ½" NPT

Vac-0-15,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PFQ-ZR** StabilizR™

2.5" (63mm)  
4" (100mm)

Bronce al Fósforo/Latón

¼" o ½" NPT

Vac-0-10,000 psi/bar,  
psi/kg/cm<sup>2</sup>



**PLP** Baja Presión

2.5" (63mm)  
4" (100mm)  
4.5" (115mm)  
6" (150mm)

316 SS/Latón

¼" NPT

Vac-0-10 psi/bar,  
psi/kg/cm<sup>2</sup>



**PSC** Caja de Seguridad

2.5" (63mm)  
4" (100mm)  
4.5" (115mm)  
6" (150mm)

316L SS

¼" o ½" NPT

Vac-0-20,000 psi/bar, psi/kg/cm<sup>2</sup>  
Tri-Clamp® is a registered trademark of Tri-Clover, Inc.



**PSP** Tubo Espiral

1" (25mm), 1.125" (30mm)  
1.25" (32mm), 1.5" (40mm)

304 SS/Bronce al Berililio/Latón

⅙" NPT

0-5,000 psi/bar, psi/kg/cm<sup>2</sup>



**PTG** Pruebas

4" (100mm)  
6" (150mm)  
Dial con aspejo de antiparalaje

316 SS/Latón

¼" o ½" NPT

Vac-0-10,000 psi/bar, psi/kg/cm<sup>2</sup>



**PTS** Tube Stub

2.5" (63mm)

316L SS

¼" tube stub

Vac-0-5,000 psi/bar, psi/kg/cm<sup>2</sup>



**PWL** Soldadura

1.5" (40mm)  
2" (50mm)  
2.5" (63mm)

Bronce al Fósforo/Latón

1.5" carátula: ⅙" NPT  
2", 2.5" carátula: ¼" NPT

0-4,000 psi/bar, psi/kg/cm<sup>2</sup>